

## CH1-8294



<b>Radio Model</b>	Motorola XTS3000/5000, MTP300
<b>Battery Model</b>	AM8294, AM8294-17, AM8299N, AM8299N-27, AM8299N-40, AM8610Li, NTN8294, NTN8923, RNN4006
<b>Mechanical Characteristics</b>	
<b>Dimension</b>	132.1 X 113.8 X 67.8 mm
<b>Weight</b>	Approx. 230g - <i>without PSU</i> Approx. 800g - <i>with PSU</i>
<b>Plastic Material</b>	ABS+PC
<b>Charge Status Display</b>	Dual LED display
<b>Electrical Characteristics</b>	
<b>Chemistry Supported</b>	Ni-Cd, Ni-MH, Li-ion
<b>Input voltage</b>	12V
<b>Max. Charge Current</b>	1000mA
<b>Power supply</b>	External with safety approval
<b>AC Input</b>	110V, 230V, and 240V
<b>Charge Time</b>	1 ~ 4 hours depend on battery type
<b>Charge Mode</b>	Ni-Cd / Ni-MH: Constant current Lithium Ion: Constant current to constant voltage
<b>Temperature</b>	-5 ~ +40°C (+23 ~ +104°F)
<b>Agency approval</b>	CE for the charging unit