



CH1-FNB57



| Radio Model | Yeasu Vertex Standard VX-160/180/210A/410/420/800* |
|----------------------------|--|
| Battery Model | AY-FNB57, AY-FNB57N, AY-FNB64, AYN-FNB64N, FNB- |
| - | V57, FNB-64, FNB-V67Li, FNB-62* |
| Mechanical Characteristics | |
| Dimension | 132.1 X 113.8 X 67.8 mm |
| Weight | Approx. 230g - without PSU |
| | Approx. 800g - with PSU |
| Plastic Material | ABS+PC |
| Charge Status Display | Dual LED display |
| Electrical Characteristics | |
| Chemistry Supported | Ni-Cd, Ni-MH, Li-ion |
| Input voltage | 12V |
| Max. Charge Current | 1000mA |
| Power supply | External with safety approval |
| AC Input | 110V, 230V, and 240V |
| Charge Time | 1 ~ 3 hours depend on battery type |
| Charge Mode | Ni-Cd / Ni-MH: Constant current |
| | Lithium Ion: Constant current to constant voltage |
| Temperature | -5 ~ +40°C (+23 ~ +104°F) |
| Agency approval | CE for the charging unit |

^{*} Only charge FNB-62 battery alone or with VX-800 radio.

